



Comparison Chart for GV-Edge Recording Manager Versions

Software Functions	Windows Version	Mac Version
Camera & Host Settings		
Enable/Disable Camera Monitoring	Yes	Yes
Camera/Host Auto-Scanning	Yes	Yes
Camera IP Auto-Assigning	Yes	Yes
ID/Password Setting	Yes	Yes
Information Display (MAC address, F/W Version, Model)	Yes	Yes
Device Name	Yes	Yes
Support for Authentication Server ¹	Yes	N/A
Output Trigger	Yes	N/A
Live View		
PTZ Control	Yes	Yes (Auto Pan functions not supported)
Recording Status Indicator (Monitoring / Non-monitoring)	Yes	Yes
Max. Number of Channels	64	64
Channel	Free	4, 6, 8, 9, 10, 13, 16, 25, 36
Division	With License	4, 6, 8, 9, 10, 13, 16, 25, 36, 49, 64 (With GV-USB Dongle)
Customized Division Layout	Yes	4, 6, 8, 9, 10, 13, 16, 25, 36 4, 6, 8, 9, 10, 13, 16, 25, 36, 64 (In-App Purchase)
Image Drag and Drop	N/A	N/A
Image Rotation (0°, 90°, 180°, 270°)	N/A	Yes
Snapshot	Yes	Yes
Viewing Options (PIP view, PAP view)	Yes	Yes
Wide Angle	Yes	N/A
Screen Setting (Fitting Window / Fixed Ratio change)	Yes	Yes
Fisheye Dewarping	Yes	Yes (Object Track, Auto Pan and Guard Tour Setting not supported)
Audio	2-way	1-way
On-Demand (Dual Streaming)	Yes	Yes
Fisheye Dual Streaming	Yes	Yes
Saving Layout from Different Hosts	Yes	N/A
Corridor-Mode Live View Display	Yes	Yes
QView Display ²	Yes	N/A
Support for GV-VMS Heat Map analysis	Yes	N/A
Support for H.265 Codec	Yes	Yes
Displaying channels from GV-VMS Trial version	Yes	Yes
Playback		
Timeline Mode	N/A	Yes
Max. Number of Channels	1	1
Play Speed ³	Yes	Yes
Remote ViewLog Player ⁴	Yes	N/A
NAS Settings		
NAS Setup (Path, ID/Password, Search)	Yes	Yes
Storage Information	Yes	Yes



NAS / SNVR Playback	
Video Clip Download	Yes
Video Analytics Playback (Fisheye Dewarping, Defog, Stabilizer)	Yes
Supported Hosts	
For Windows and Mac OS X	GV-IP Camera, GV-Video Server (VS11, VS12, VS14, VS2400/2420), GV-System (GV-DVR/NVR), GV-VMS, GV-Recording Server, GV-SNVR

All specifications are subject to change without notice.

Note:

1. GV-Edge Recording Manager can integrate with the Authentication Server to perform live view and playback of the devices under a specified GV-VMS or GV-System account.
2. QView Display enables the projection of a live view display onto one other monitor.
3. The Play Speed option is not supported in GV-SNVR.
4. A maximum of 16 channels can be supported in the Remote ViewLog Player.
5. GV-Edge Recording Manager (Mac Version) does not support GV-SD2322-IR, GV-SD3732-IR, GV-EBD4700, and GV-ABL / ADR / ABD1300.