

Architectural and Engineering Specifications

GV-Box Camera

Revision Date: 09/23/2020

The document is written using industry standard formatting and language, and is designed for use by architects, consultants, and specifying engineers who are preparing bid specifications for security cameras, surveillance systems and access control systems.

The electronic version of these specifications may be copied into the appropriate sections of a complete bid specification by using the “cut and paste” method. They are written to highlight the features and specifications of GeoVision products. Section headings mention specific models only for clarity – these may be deleted after insertion into the complete specification.

*Product covered in this document includes:
GV-BX2500 Series*

GV-BX2500 is a brand-new model of Box Camera series. It comes with a sensor featuring Super Low Lux to provide clear images not only under contrasting light intensities but also in the darkness. The camera features a mini USB port which supports wireless connection through a GV-WiFi Adapter (optional) or external storage using a USB hard drive.

All specifications are subject to change without prior notice. For more information on GeoVision products, please visit www.geovision.com.tw.

GV-Box Camera



GV-BX2500-8F



GV-BX2500-3V

A. General Requirements

1. The camera shall be a dual-stream, day/night, network camera equipped with the following image sensor:

Models	Image Sensor
GV-BX2500 Series	1/2.8" progressive scan super low lux CMOS

2. The main stream shall utilize H.264 and MJPEG video compression methods with the maximum resolution and frame rate as below:

Models	Max. Resolution & Frame Rate
GV-BX2500 Series	1920 x 1080 at 30 fps (60/50 Hz)

3. The sub stream shall utilize H.264 and MJPEG video compression methods with a resolution up to 448 x 252 at a maximum frame rate of 30 fps.
4. Live view shall be accessible through network and TV monitor using a video-out wire with BNC connector. The resolution for TV-out shall be up to 720 x 486 for NTSC, and up to 720 x 576 for PAL.

5. The maximum number of streams supported for the camera over the network using the H.264 codec is described as below.

Models	Max. Number of Streams
GV-BX2500 Series	8

When the camera is connected to video management software GV-DVR / NVR / VMS, it shall take up two (2) streams and when it is connected to IE browser or any other application, it shall take up one (1) stream.

6. The camera shall provide administrator and guest account settings on the Web interface. The administrator account shall have full access to all the functions, and the guest account shall only have access to camera live view and network status information.

B. Alarm and Notification Requirements

1. The camera shall be capable of motion detection.
2. A privacy mask function shall be provided for users to specify areas to be blocked off on the camera view for privacy purpose.
3. The camera shall support tampering alarm such that an E-mail notification or an output device shall be triggered when the camera is being tampered.
4. The camera shall support visual automation function such that the connected output devices can be triggered by clicking its image on the live view.
5. The camera shall be capable of triggering an output device or sending E-mail alert when recording errors occur and when the memory card is full.
6. The camera shall have E-mail and FTP ability for alert notification. When motion is detected, a captured still image will be sent by E-mail or to the FTP server.
7. The camera shall be capable of integration with video management software or a central monitoring station. The video or text alerts shall be sent upon alarm event.

C. Recording and Playback Requirements

1. The camera shall be capable of beginning recording according to a schedule, upon input trigger, and upon motion detection.
2. The camera shall be capable of storing recorded data on an inserted micro SD/SDHC memory card (Class 10), an FTP server, GV-DVR / NVR / VMS, and GV-Recording Server.
3. Scheduled backup shall be supported when connected to a server installed with the GV-Backup Center program.
4. Pre-recording and post-recording functions shall be available.
5. Users shall be able to play back recorded data over network or on a video surveillance or management software GV-DVR / NVR / VMS.

D. Video Requirements

1. The camera shall support both constant bitrate (CBR) and variable bitrate (VBR). For variable bitrate (VBR), the maximal bit rate shall be selectable to restrict the system from exceeding a specified bit rate.
2. The following white balance settings shall be selectable on the Web interface: auto, indoor, outdoor, fluorescent and manual. The manual white balance range shall be approximately 2800 degrees to 8500 degrees Kelvin.
3. The camera shall have an automatic and manual shutter with the speed range of 1/5 – 1/8000 seconds.
4. The camera shall support the following image adjustment on the Web interface: image brightness, contrast, saturation, sharpness, gamma, white balance, flicker-less, image orientation, shutter speed, D/N sensitivity and software WDR.
5. The camera shall support the super low lux function with which the camera can display color live views in near darkness, with minimum illumination as described below.

Models	Minimum Illumination
GV-BX2500 Series	0.02 lux in color and B/W mode 0 lux with IR on

6. The camera shall support three (3) aspect ratios: 4:3, 16:9 and 5:4.

GV-BX2500 Series	Main Stream	4:3	1280 x 960, 640 x 480, 320 x 240
		16:9	1920 x 1080 (Default), 1280 x 720, 640 x 360, 448 x 252
		5:4	1280 x 1024, 640 x 512, 320 x 256
	Sub Stream	4:3	640 x 480, 320 x 240
		16:9	640 x 360, 448 x 252 (Default)
		5:4	640 x 512, 320 x 256

7. The S/N ratio for the camera shall be as described below.

Models	S/N Ratio
GV-BX2500 Series	52 dB

E. Audio Requirements

1. The camera shall support audio codec G.711.
2. The camera shall support two-way audio transmission.
3. The camera shall contain a built-in microphone.
4. The camera shall be equipped with stereo phone jacks (3.5 mm / 0.14") for an external microphone and a speaker.

F. Networking Requirements

1. The camera shall be equipped with a 10/100 Ethernet, RJ-45 connector as a network interface.
2. The camera shall be built with a Web server with which the live view is accessible using Web browsers, without the need for special viewer software.
3. The camera shall support the following network protocols: DHCP, DynDNS, FTP, HTTP, HTTPS, NTP, ONVIF (Profile S), PSIA, QoS (DSCP), RTSP, SNMP, SMTP, TCP, UDP, UPnP, 3GPP/ISMA
4. Port settings shall be configurable.
5. The camera shall be able to filter or allow specific IP addresses to restrict access to the camera.

6. QoS (DSCP) shall be supported to allow differentiated bandwidth control.
7. The camera shall be able to connect to WiFi. To initiate Wifi connection, the camera's wireless LAN shall be IEEE802.11 b/g/n. The antenna shall be external, and the security protocols shall be WEP, WPA-PSK (TKIP), WPA-PSK (AES), WPA2-PSK (TKIP), WPA2-PSK (AES).

G. Lens Requirements

1. The camera shall be equipped with a lens of the lens type and focal length as below.

Models	Lens Type	Focal Length
GV-BX2500-8F	Fixed	2.8 mm
GV-BX2500-3V	Fixed , P-Iris	3 ~ 10.5 mm

2. The camera shall contain an IR-cut filter to switch the camera from color to monochrome mode automatically by sensing the illumination level or via an input device.
3. The camera shall have an electronic day/night function.
4. The maximum aperture of the camera shall be listed below.

Models	Maximum Aperture
GV-BX2500-8F	F/1.8
GV-BX2500-3V	F/1.4

5. The camera shall be of CS lens mount.
6. The camera shall have the image format as below.

Models	Image Format
GV-BX2500-8F	1/2.5"
GV-BX2500-3V	1/2.7"

7. The camera shall support automatic gain control.
8. The horizontal field of view for each model shall be as described below.

Models	Horizontal FOV
GV-BX2500-8F	107°
GV-BX2500-3V	96° ~ 34°

H. Mechanical Requirements

1. The camera shall be equipped with interface for 1 sensor input (dry contact) and 1 alarm output (200 mA, 5V DC).
2. The camera shall have a dimension (without the lens) of 75.5 x75 x 54 mm (2.97" x 2.95" x 2.13").
3. The camera shall have a weight of 300 g (0.66 lb).
4. The camera shall have a built-in temperature detector to detect the chipset temperature inside the camera.
5. The camera shall have a mini USB slot for connecting a compatible WiFi Adapter or a USB hard drive. The USB hard drive shall meet these requirements:
 - The USB hard drive shall be of 2.5" or 3.5", version 2.0 or above.
 - The USB hard drive's storage capacity shall not exceed 2TB.
 - USB flash drives and USB hubs are not supported.
 - The USB hard drive shall require external power supply.

I. Power Requirements

1. Power shall be connected using the supplied power adapter or the Power over Ethernet (PoE).
2. The camera shall be capable of receiving power from 12V DC and IEEE 802.3af Power over Ethernet (PoE).
3. The maximum power consumption for the camera shall be 7.99 W for DC-driven iris; 6.42 W for P-Iris

J. Environmental Requirements

1. The camera shall be able to tolerate between 0°C ~ 50°C (32°F ~ 122 °F) at startup and during operation.
2. The humidity shall be within the range of 10% to 90% with no condensation.

K. System Requirements

1. The camera shall be accessible through Web browsers including Microsoft Internet Explorer (version 7 or later), Google Chrome, Mozilla Firefox and Safari.

L. Language Requirements

1. The camera shall support 31 languages on the Web interface, including Arabic, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Lithuanian, Norwegian, Persian, Polish, Portuguese, Romanian, Russian, Serbian, Simplified Chinese, Slovakian, Slovenian, Spanish, Swedish, Thai, Traditional Chinese and Turkish.

M. Applications

1. The camera shall support the following software for network storage:
 - Video surveillance or management software: GV-DVR / NVR / VMS
 - Backup and Recording software: GV-Recording Server, GV-Backup Center
2. The camera shall support smart device access using GV-Eye mobile app. for live view display and remote playback.
3. The camera shall allow remote access from central management stations, such as GV-Control Center, GV-Center V2 and GV-Vital Sign Monitor.

N. Packing List shall include:

1. Box Camera
2. Terminal Block
3. Fixed Focal or Varifocal Megapixel Lens
4. Six Lens Rings
5. Video Out Wire
6. Camera Holder
7. Holder Screw x 2
8. Power Adapter
9. GV-IPCAM H.264 Software DVD
10. GV-NVR Software DVD
11. Warranty Card

O. Certifications and Approvals

1. CE, FCC, LVC, RCM, RoHS Compliant