

## Architectural and Engineering Specifications

### GV-Target Fixed Dome

Revision Date: 09/23/2020

*The document is written using industry standard formatting and language, and is designed for use by architects, consultants, and specifying engineers who are preparing bid specifications for security cameras, surveillance systems and access control systems.*

*The electronic version of these specifications may be copied into the appropriate sections of a complete bid specification by using the “cut and paste” method. They are written to highlight the features and specifications of GeoVision products. Section headings mention specific models only for clarity – these may be deleted after insertion into the complete specification.*

*Products covered in this document include:*

*GV-EFD2700 Series*

*The Target Mini Fixed Dome (GV-EFD) is an indoor, fixed, mini-sized network camera equipped with a removable IR-cut filter and IR LEDs for day and night surveillance. Adjustable in 2 axes (pan and tilt), it offers an entry-level surveillance solution with all the essential features and excellent image quality. The camera comes with a built-in micro SD card slot for local storage and digital I/O for external connections. The camera supports H.265 video codec to achieve better compression ratio while maintaining high quality pictures at reduced network bandwidths. With the super low lux CMOS image sensor, the camera is capable of providing a color live view in near darkness.*

All specifications are subject to change without prior notice. For more information on GeoVision products, please visit [www.geovision.com.tw](http://www.geovision.com.tw).

## GV-Target Fixed Dome



### A. General Requirements

1. The camera shall be a dual-stream, day/night, network camera equipped with the following image sensor:

Models	Image Sensor
GV-EFD2700 Series	1/2.8" progressive scan super low lux CMOS

2. The main stream shall utilize H.265 and H.264 video compression methods with the maximum resolution and frame rate as below:

Models	Max. Resolution & Frame Rate
GV-EFD2700 Series	1920 x 1080 at 25 fps (50 Hz)
	1920 x 1080 at 30 fps (60 Hz)

3. The sub stream shall utilize H.265 H.264 and MJPEG video compression methods with a resolution up to 640 x 480 at a maximum frame rate of 30 fps.

4. The maximum number of streams supported for the camera over the network, using the H.265 codec is eight (8) streams. When the camera is connected to video surveillance or management software GV-DVR/NVR/VMS, it shall take up two (2) streams and when it is connected to IE browser or any other application, it shall take up one (1) stream.
5. The camera shall provide administrator and guest account settings on the Web interface. The administrator account shall have full access to all the functions, and the guest account shall only have access to camera live view and network status information.

#### B. Alarm and Notification Requirements

1. The camera shall be capable of motion detection.
2. A privacy mask function shall be provided for users to specify areas to be blocked off on the camera view for privacy purpose. The function shall also be supported through ONVIF/RTSP connection.
3. The camera shall support tampering alarm such that an E-mail notification, an alarm or an output device, shall be triggered when the camera is being tampered.
4. The camera shall support visual automation function such that the connected output devices can be automated from live view.
5. The camera shall be capable of triggering an output device or sending E-mail alert when recording errors occur and when the memory card is full.
6. The camera shall have E-mail and FTP ability for alert notification. When motion is detected, a captured still image will be sent by E-mail or to the FTP server.
7. The camera shall be capable of integration with video surveillance/management software or a central monitoring station. The video or text alerts shall be sent upon alarm event.

#### C. Recording and Playback Requirements

1. The camera shall be capable of beginning recording according to a schedule, upon input trigger, and upon motion detection.
2. The camera shall be capable of storing recorded data on a built-in micro SD/SDHC/UHS-1 memory card, GV-DVR/NVR/VMS, and GV-Recording Server.
3. Pre-recording and post-recording functions shall be available.
4. Users shall be able to play back recorded data over network or on a video surveillance or management software GV-DVR/NVR/VMS.

D.

#### D. Video Requirements

1. The camera shall support both constant bitrate (CBR) and variable bitrate (VBR). For variable bitrate (VBR), the maximal bit rate shall be selectable to restrict the system from exceeding a specified bit rate.
2. The camera shall support Smart Streaming function, with which the bitrates will be automatically reduced in static scenes, significantly maximizing bandwidth and lowering file size. It only works with compatible version of GV-DVR/NVR/VMS.
3. The following white balance settings shall be selectable on the Web interface: auto and manual. The manual white balance range shall be approximately 2800 degrees to 8500 degrees Kelvin.
4. The camera shall have an automatic and manual shutter with the speed range of 1/5 – 1/16000 seconds.
5. The camera shall support the following image adjustment on the Web interface: image brightness, contrast, saturation, sharpness, gamma, white balance, flicker-less, image orientation, shutter speed, backlight compensation, D/N sensitivity, WDR/WDR Pro, defog, low lux enhancement, denoise and metering.

6. The camera shall support three (3) aspect ratios: 4:3, 16:9 and 5:4.

<b>GV-EFD2700 Series</b>	<b>Main Stream</b>	<b>4:3</b>	1280 x 960, 640 x 480
		<b>16:9</b>	1920 x 1080 (Default), 1280 x 720, 640 x 360
		<b>5:4</b>	1280 x 1024, 640 x 512
	<b>Sub Stream</b>	<b>4:3</b>	640 x 480, 320 x 240
		<b>16:9</b>	640 x 360 (Default), 448 x 256
		<b>5:4</b>	640 x 512, 320 x 256

7. The S/N ratio for the camera shall be as described below.

<b>Models</b>	<b>S/N Ratio</b>
GV-EFD2700 Series	56 dB

#### E. Audio Requirements

1. The camera shall support audio codec G.711.
2. The camera shall support one-way audio transmission.
3. The camera shall have a built-in microphone.

#### F. Networking Requirements

1. The camera shall be equipped with a 10/100 Ethernet, RJ-45 connector as a network interface.
2. The camera shall be built with a Web server with which the live view is accessible using Web browsers, without the need for special viewer software.
3. The camera shall support the following network protocols: DHCP, DynDNS, FTP, HTTP, HTTPS, NTP, ONVIF (Profile S), QoS (DSCP), RTSP, SNMP, SMTP, TCP, UDP, UPnP and 3GPP/ISMA.
4. Port settings shall be configurable.
5. The camera shall be able to filter or allow specific IP addresses to restrict access to the camera.
6. QoS (DSCP) shall be supported to allow differentiated bandwidth control.

### G. Lens Requirements

1. The camera shall be equipped with a lens of the lens type and focal length as below.

Models	Lens Type	Focal Length
GV-EFD2700-0F	Fixed	2.8 mm
GV-EFD2700-2F		3.8 mm

2. The camera shall be equipped with a removable IR-cut filter to switch from color to monochrome mode automatically by sensing the illumination level.
3. The maximum aperture of the camera shall be as below.

Models	Max. Aperture
GV-EFD2700-0F	F/2.0
GV-EFD2700-2F	F/1.8

4. The camera shall be of M12 (pitch 0.5mm) lens mount.
5. The camera shall have the image format as below.

Models	Image Format
GV-EFD2700 Series	1/2.7 inch

6. The camera shall support automatic gain control.
7. The dynamic range for the camera shall be as described below.

Models	Dynamic Range
GV-EFD2700 Series	Up to 130 dB

8. The horizontal field of view for each model shall be as described below.

Models	Horizontal FOV
GV-EFD2700-0F	100°
GV-EFD2700-2F	73°

9. The camera shall have the minimum illumination as described below.

Models	Minimum Illumination
GV-EFD2700 Series	0.005 lux in color mode
	0.004 lux in B/W mode
	0 lux with IR on

10. The camera shall be equipped with 12 IR LEDs with the maximum IR distance of 40 m (131 ft).

#### H. Mechanical Requirements

1. The camera shall adopt a 3-axis design and be able to pan ( $-45^{\circ} \sim 45^{\circ}$ ), and tilt ( $0^{\circ} \sim 63^{\circ}$ ).
2. The camera shall be equipped with interface for 1 sensor input (dry contact) and 1 alarm output (200 mA, 5V DC).
3. The camera shall have a dimension of  $\varnothing$  100 (diameter) x 60 (height) mm (3.9" x 2.4").
4. The camera shall have a weight of 148 g (0.33 lb).
5. The camera shall have a built-in temperature detector to detect the chipset temperature inside the camera.
6. The camera shall support ceiling and wall installation with the standard package.

#### I. Power Requirements

1. Power shall be connected using a power adapter or the Power over Ethernet (PoE).
2. The camera shall be capable of receiving power from 12V DC and IEEE802.3af Power over Ethernet (PoE).
3. The maximum power consumption shall be 6.07 W.

#### J. Environmental Requirements

1. The camera shall be able to tolerate between  $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$  ( $32^{\circ}\text{F} \sim 113^{\circ}\text{F}$ ).
2. The humidity shall be within the range of 10% to 90% with no condensation.

#### K. System Requirements

1. The camera shall be accessible through Web browsers including Microsoft Internet Explorer (version 8.0 or later), Google Chrome, Mozilla Firefox and Safari.

#### L. Language Requirements

1. The camera shall support 31 languages on the Web interface, including Arabic, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Lithuanian, Norwegian, Persian, Polish, Portuguese, Romanian, Russian, Serbian, Simplified Chinese, Slovakian, Slovenian, Spanish, Swedish, Thai, Traditional Chinese and Turkish.

M. Applications

1. The camera shall support the following software for network storage:
  - Video surveillance and management software: GV-DVR/NVR/VMS
  - Backup and Recording software: GV-Edge Recording Manager, GV-Recording Server, GV-Redundant / Failover Server
2. The camera shall support smart device access using GV-Eye mobile app. for live view display and remote playback.
3. The camera shall allow remote access from central management stations, such as GV-Control Center, GV-Center V2 and GV-Vital Sign Monitor.

N. Packing List shall include:

1. H.265 Mini Fixed Dome
2. Screw x 2
3. Screw Anchor x 2
4. Focus Adjustment Ring
5. GV-IPCAM Software DVD
6. GV-Software DVD
7. Warranty Card

O. Certifications and Approvals

1. CE, FCC, RCM, LVD, RoHS Compliant