

## Architectural and Engineering Specifications

### GV-Mini Fixed Dome

Revision Date: 09/23/2020

*The document is written using industry standard formatting and language, and is designed for use by architects, consultants, and specifying engineers who are preparing bid specifications for security cameras, surveillance systems and access control systems.*

*The electronic version of these specifications may be copied into the appropriate sections of a complete bid specification by using the “cut and paste” method. They are written to highlight the features and specifications of GeoVision products. Section headings mention specific models only for clarity – these may be deleted after insertion into the complete specification.*

*Products covered in this document include:*

*GV-MFD1501 Series*

*The Mini Fixed Dome (GV-MFD) series is designed for indoor surveillance. The GV-MFD cameras are fixed, mini-sized ceiling-mount network solution, adjustable in 2 axis (pan and tilt) and support PoE.*

All specifications are subject to change without prior notice. For more information on GeoVision products, please visit [www.geovision.com.tw](http://www.geovision.com.tw).

## GV-Mini Fixed Dome Camera



### A. General Requirements

1. The camera shall be a dual-stream, day/night, network camera equipped with the following image sensor:

| Models            | Image Sensor                             |
|-------------------|------------------------------------------|
| GV-MFD1501 Series | 1/3" progressive scan super low lux CMOS |

2. The main stream shall utilize H.264 and MJPEG video compression methods with the maximum resolution and frame rate as below:

| Models            | Max. Resolution & Frame Rate     |
|-------------------|----------------------------------|
| GV-MFD1501 Series | 1280 x 1024 at 30 fps (60/50 Hz) |

3. The sub stream shall utilize H.264 and MJPEG video compression methods with a resolution up to 640 x 512 at a maximum frame rate of 30 fps.
4. The maximum numbers of streams supported for the camera over the network, using the H.264 codec are described as below.

| Models            | Max. Number of Streams |
|-------------------|------------------------|
| GV-MFD1501 Series | 8                      |

When the camera is connected to GV-System (GV-DVR/NVR) or GV-VMS, video management software, it shall take up two (2) streams and when it is connected to IE browser or any other application, it shall take up one (1) stream.

5. The camera shall provide administrator and guest account settings on the Web interface. The administrator account shall have full access to all the functions, and the guest account shall only have access to camera live view and network status information.
6. The camera shall be available in black or white housing.

#### B. Alarm and Notification Requirements

1. The camera shall be capable of motion detection.
2. A privacy mask function shall be provided for users to specify areas to be blocked off on the camera view for privacy purpose. The function shall also be supported through ONVIF/RTSP connection.
3. The camera shall support tampering alarm such that an E-mail notification shall be sent when the camera is being tampered.
4. The camera shall be capable of sending E-mail alert when recording errors occur and when the memory card is full.
5. The camera shall have E-mail and FTP ability for alert notification. When motion is detected, a captured still image will be sent by E-mail or to the FTP server.
6. The camera shall be capable of integration with video management software or a central monitoring station. The video or text alerts shall be sent upon alarm event.

#### C. Recording and Playback Requirements

1. The camera shall be capable of beginning recording according to a schedule and upon motion detection.
2. The camera shall be capable of storing recorded data on an inserted micro SD/SDHC memory card (version 2.0, Class 10), an FTP server, GV-Systems (GV-DVR/NVR), GV-Backup Center and GV-Recording Server, GV-VMS, and GV-NAS System.
3. Scheduled backup shall be supported when connected to a server installed with the GV-Backup Center program.
4. Pre-recording and post-recording functions shall be available.
5. Users shall be able to play back recorded data over network or on a video management software, GV-System (GV-DVR/NVR) or GV-VMS.

#### D. Video Requirements

1. The camera shall support both constant bitrate (CBR) and variable bitrate (VBR). For variable bitrate (VBR), the maximal bit rate shall be selectable to restrict the system from exceeding a specified bit rate.
2. The following white balance settings shall be selectable on the Web interface: auto, indoor, outdoor, fluorescent and manual. The manual white balance range shall be approximately 2800 degrees to 8500 degrees Kelvin.
3. The camera shall have an automatic and manual shutter with the speed range of 1/5 – 1/8000 seconds.
4. The camera shall support the following image adjustment on the Web interface: image brightness, contrast, saturation, sharpness, gamma, white balance, flicker-less 50/60 Hz, image orientation, shutter speed, backlight compensation, D/N sensitivity, WDR, defog, super low lux, denoise, and metering.
5. The camera shall support the super low lux function with which the camera can display color live views in near darkness, with minimum illumination of 0.01 lux for color and B/W.
6. The camera shall support three (3) aspect ratios: 4:3, 16:9 and 5:4.

|                          |                    |             |                                                |
|--------------------------|--------------------|-------------|------------------------------------------------|
| <b>GV-MFD1501 Series</b> | <b>Main Stream</b> | <b>4:3</b>  | 1280 x 960, 640 x 480, 320 x 240               |
|                          |                    | <b>16:9</b> | 1280 x 720, 640 x 360, 448 x 252               |
|                          |                    | <b>5:4</b>  | 1280 x 1024 (Default),<br>640 x 512, 320 x 256 |
|                          | <b>Sub Stream</b>  | <b>4:3</b>  | 640 x 480, 320 x 240                           |
|                          |                    | <b>16:9</b> | 640 x 360, 448 x 252                           |
|                          |                    | <b>5:4</b>  | 640 x 512, 320 x 256 (Default)                 |

7. The S/N ratio for the camera shall be as described below.

| <b>Models</b>     | <b>S/N Ratio</b> |
|-------------------|------------------|
| GV-MFD1501 Series | 55 dB            |

#### E. Audio Requirements

1. The camera shall support audio codec G.711.
2. The camera shall support two-way audio transmission.
3. The camera shall contain a built-in microphone.
4. The camera shall be equipped with an RCA female connector for an external speaker.

#### F. Networking Requirements

1. The camera shall be equipped with a 10/100 Ethernet, RJ-45 connector as a network interface.
2. The camera shall be built with a Web server with which the live view is accessible using Web browsers, without the need for special viewer software.
3. The camera shall support the following network protocols: DHCP, DynDNS, FTP, HTTP, HTTPS, NTP, ONVIF (Profile S), PSIA, QoS (DSCP), RTSP, SNMP, SMTP, TCP, UDP, UPnP and 3GPP/ISMA.
4. Port settings shall be configurable.
5. The camera shall be able to filter or allow specific IP addresses to restrict access to the camera.
6. QoS (DSCP) shall be supported to allow differentiated bandwidth control.

#### G. Lens Requirements

1. The camera shall be equipped with a lens of the lens type and focal length as below.

| Models        | Lens Type  | Focal Length |
|---------------|------------|--------------|
| GV-MFD1501-0F | Fixed lens | 2.8 mm       |
| GV-MFD1501-1F |            | 4 mm         |
| GV-MFD1501-2F |            | 8 mm         |
| GV-MFD1501-3F |            | 12 mm        |
| GV-MFD1501-4F |            | 2.1 mm       |
| GV-MFD1501-5F |            | 3.8 mm       |

2. The camera shall have an electronic day/night function.

3. The maximum aperture of the camera shall be as below.

| Models        | Max. Aperture |
|---------------|---------------|
| GV-MFD1501-0F | F/2.0         |
| GV-MFD1501-1F | F/1.5         |
| GV-MFD1501-2F | F/1.6         |
| GV-MFD1501-3F | F/1.6         |
| GV-MFD1501-4F | F/1.8         |
| GV-MFD1501-5F | F/1.8         |

4. The camera shall be of M12 lens (Pitch 0.5 mm).
5. The camera shall have the image format of 1/3 inch.
6. The camera shall support automatic gain control.
7. The dynamic range for each model shall be as described below.

| Models            | Dynamic Range |
|-------------------|---------------|
| GV-MFD1501 Series | Up to 72 dB   |

8. The horizontal field of view for each model shall be as described below.

| Models        | Horizontal FOV |
|---------------|----------------|
| GV-MFD1501-0F | 87°            |
| GV-MFD1501-1F | 67°            |
| GV-MFD1501-2F | 35°            |
| GV-MFD1501-3F | 22°            |
| GV-MFD1501-4F | 124°           |
| GV-MFD1501-5F | 64°            |

9. The camera shall have the minimum illumination as described below.

| Models             | Minimum Illumination           |
|--------------------|--------------------------------|
| GV- MFD1501 Series | 0.01 lux in color and B/W mode |

#### H. Mechanical Requirements

- The camera shall adopt a 2-axis design and be able to pan (-45° ~ 45°) and tilt (0° ~ 90°)
- The camera shall have a dimension of ø 106 x 53.9 mm (4.2" x 2.1").
- The camera shall have a weight of 280 g (0.62 lb).

4. The camera shall have a built-in temperature detector to detect the chipset temperature inside the camera.
  5. The camera shall have a USB slot for connecting a compatible WiFi Adapter or a USB hard drive. The USB hard drive shall meet these requirements:
    - The USB hard drive shall be of 2.5" or 3.5", version 2.0 or above.
    - The USB hard drive's storage capacity shall not exceed 2 TB.
    - USB flash drives and USB hubs are not supported.
    - The USB hard drive shall require external power supply.
- I. Power Requirements
1. Power shall be connected using the supplied power adapter or the Power over Ethernet (PoE).
  2. The camera shall be capable of receiving power from 5V DC and IEEE 802.3af Power over Ethernet (PoE).
  3. The maximum power consumption for the camera shall be 6 W.
- J. Environmental Requirements
1. The camera shall be able to tolerate between 0°C ~ 50°C (32°F ~ 122°F) at startup and during operation.
  2. The humidity shall be within the range of 10% to 90% with no condensation.
- K. System Requirements
1. The camera shall be accessible through Web browsers including Microsoft Internet Explorer (version 7.0 or later), Google Chrome, Mozilla Firefox and Safari.
- L. Language Requirements
1. The camera shall support 31 languages on the Web interface, including Arabic, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Lithuanian, Norwegian, Persian, Polish, Portuguese, Romanian, Russian, Serbian, Simplified Chinese, Slovakian, Slovenian, Spanish, Swedish, Thai, Traditional Chinese and Turkish.

#### M. Applications

1. The camera shall support the following software for network storage:
  - Video management software: GV-System (GV-DVR/NVR), GV-VMS
  - Backup and Recording software: GV-Backup Center, GV-Recording Server
  - NAS system: GV-NAS System
2. The camera shall support smart device access using GV-Eye mobile app. for live view display and remote playback.
3. The camera shall allow remote access from central management stations, such as GV-Control Center, GV-Center V2 and GV-Vital Sign Monitor.

#### N. Packing List shall include:

1. Mini Fixed Dome
2. Torx Wrench
3. Self Tapping Screw x 2
4. Screw Anchor x 2
5. Cable Stopper x 1
6. Short-Body RJ-45 Plug
7. USB/Audio Y-Cable
8. Power Adapter
9. GV-IPCAM H.264 Quick Start Guide
10. GV-IPCAM H.264 Software DVD
11. GV-NVR Quick Start Guide
12. GV-NVR Software DVD

#### O. Certifications and Approvals

1. CE, FCC, RCM, RoHS Compliant