

## Architectural and Engineering Specifications

### GV-Ultra Bullet Camera

Revision Date: 06/18/2014

*The document is written using industry standard formatting and language, and is designed for use by architects, consultants, and specifying engineers who are preparing bid specifications for security cameras, surveillance systems and access control systems.*

*The electronic version of these specifications may be copied into the appropriate sections of a complete bid specification by using the “cut and paste” method. They are written to highlight the features and specifications of GeoVision products. Section headings mention specific models only for clarity – these may be deleted after insertion into the complete specification.*

*Products covered in this document include:*

*GV-UBL1301 Series*

*The Ultra Bullet Cameras are light-weighted cameras designed for outdoor environments. They adhere to the IP67 standard and have full protection against dust and jets of water.*

All specifications are subject to change without prior notice. For more information on GeoVision products, please visit [www.geovision.com.tw](http://www.geovision.com.tw).

## GV-Ultra Bullet Camera



### A. General Requirements

1. The camera shall be a dual-stream, day/night, network camera equipped with the following image sensor:

Models	Image Sensor
GV-UBL1301 Series	1/2.5" progressive scan CMOS

2. The main stream shall utilize H.264 and MJPEG video compression methods with the maximum resolution and frame rate as below:

Models	Max. Resolution & Frame Rate
GV-UBL1301 Series	1280 x 1024 at 30 fps

3. The sub stream shall utilize H.264 and MJPEG video compression methods with a resolution up to 640 x 512 at a maximum frame rate of 30 fps.
4. The maximum numbers of streams supported for the camera over the network, using the H.264 codec are described as below.

Models	Max. Number of Streams
GV-UBL1301 Series	8

Note when the camera is connected to GV-System (GV-DVR/NVR) or GV-VMS, video management software, it shall take up two (2) streams and when it is connected to IE browser or any other application, it shall take up one (1) stream.

5. The camera shall provide administrator and guest account settings on the Web interface. The administrator account shall have full access to all the functions, and the guest account shall only have access to camera live view and network status information.

#### A. Alarm and Notification Requirements

1. The camera shall be capable of motion detection.
2. A privacy mask function shall be provided for users to specify areas to be blocked off on the camera view for privacy purpose. The function shall also be supported through ONVIF/RTSP connection.
3. The camera shall support tampering alarm such that an E-mail notification or an output device shall be triggered when the camera is being tampered.
4. The camera shall support visual automation function such that the connected output devices can be triggered by clicking its image on the live view.
5. The camera shall be capable of triggering an output device or sending E-mail alert when recording errors occur and when the memory card is full.
6. The camera shall have E-mail and FTP ability for alert notification. When motion is detected, a captured still image will be sent by E-mail or to the FTP server.
7. The camera shall be capable of integration with video management software or a central monitoring station. The video or text alerts shall be sent upon alarm event.

#### B. Recording and Playback Requirements

1. The camera shall be capable of beginning recording according to a schedule, upon input trigger, and upon motion detection.
2. The camera shall be capable of storing recorded data on an inserted micro SD/SDHC memory card (version 2.0, Class 10), an FTP server, GV-Systems (GV-DVR/NVR), GV-Backup Center and GV-Recording Server, GV-VMS, and GV-NAS System.
3. Scheduled backup shall be supported when connected to a server installed with the GV-Backup Center program.
4. Pre-recording and post-recording functions shall be available.

- Users shall be able to play back recorded data over network or on a video management software, GV-System (GV-DVR/NVR) or GV-VMS.

### C. Video Requirements

- The camera shall support both constant bitrate (CBR) and variable bitrate (VBR). For variable bitrate (VBR), the maximal bit rate shall be selectable to restrict the system from exceeding a specified bit rate.
- The following white balance settings shall be selectable on the Web interface: auto, indoor, outdoor, fluorescent and manual. The manual white balance range shall be approximately 2800 degrees to 8500 degrees Kelvin.
- The camera shall have an automatic and manual shutter with the speed range of 1/5 – 1/8000 seconds.
- The camera shall support the following image adjustment on the Web interface: image brightness, contrast, saturation, sharpness, gamma, white balance, flicker-less, image orientation, shutter speed, backlight compensation, D/N sensitivity, WDR, defog, denoise, and metering.
- The camera shall support three (3) aspect ratios: 4:3, 16:9 and 5:4.

<b>GV-UBL1301 Series</b>	<b>Main Stream</b>	<b>4:3</b>	1280 x 960, 640 x 480, 320 x 240
		<b>16:9</b>	1280 x 720, 640 x 360, 448 x 252
		<b>5:4</b>	1280 x 1024, 640 x 512, 320 x 256
	<b>Sub Stream</b>	<b>4:3</b>	640 x 480, 320 x 240
		<b>16:9</b>	640 x 360, 448 x 252
		<b>5:4</b>	640 x 512, 320 x 256

- The S/N ratio for the camera shall be as described below.

<b>Models</b>	<b>S/N Ratio</b>
GV-UBL1301 Series	45 dB

### D. Networking Requirements

- The camera shall be equipped with a 10/100 Ethernet, RJ-45 connector as a network interface.
- The camera shall be built with a Web server with which the live view is accessible using Web browsers, without the need for special viewer software.

3. The camera shall support the following network protocols: DHCP, DynDNS, FTP, HTTP, HTTPS, NTP, ONVIF (Profile S), PSIA, QoS (DSCP), RTSP, SMTP, TCP, UDP, UPnP, 3GPP/ISMA, and SNMP.
4. Port settings shall be configurable.
5. The camera shall be able to filter or allow specific IP addresses to restrict access to the camera.
6. QoS (DSCP) shall be supported to allow differentiated bandwidth control.

#### E. Lens Requirements

1. The camera shall be equipped with a lens of the lens type and focal length as below.

Models	Lens Type	Focal Length
GV-UBL1301-0F	Fixed lens	2.8 mm
GV-UBL1301-1F		4 mm
GV-UBL1301-2F		8 mm
GV-UBL1301-3F		12 mm

2. The camera shall be equipped with a removable IR-cut filter.
3. The maximum aperture of the camera shall be listed as below.

Models	Maximum Aperture
GV-UBL1301-0F	F/2.0
GV-UBL1301-1F	F/1.5
GV-UBL1301-2F	F/1.6
GV-UBL1301-3F	

4. The camera shall be of M12 lens mount.
5. The camera shall have the image format of 1/3 inch.
6. The camera shall support automatic gain control.
7. The dynamic range for each model shall be as described below.

Models	Dynamic Range
GV-UBL1301 Series	Up to 72 dB

8. The horizontal field of view for each model shall be as described below.

<b>Models</b>	<b>Horizontal FOV</b>
GV-UBL1301-0F	69°
GV-UBL1301-1F	49°
GV-UBL1301-2F	25°
GV-UBL1301-3F	16°

9. The camera shall have the minimum illumination as described below.

<b>Models</b>	<b>Minimum Illumination</b>
GV-UBL1301 Series	0.15 lux in color mode 0.10 lux in B/W mode 0 lux in B/W mode with IR on

10. The camera shall be equipped with 4 IR LEDs with the maximum IR distance described below.

<b>Models</b>	<b>Maximum IR Distance</b>
GV-UBL1301 Series	10 m (32.81 ft)

#### F. Mechanical Requirements

1. The camera shall have a dimension of 124 x 65 x 69 mm (4.9" x 2.6" x 2.7").
2. The camera shall have a weight of 730 g (1.6 lb).
3. The camera shall have a built-in temperature detector to detect the chipset temperature inside the camera.
4. The camera shall support ceiling and wall installation with the standard package.
5. The camera shall contain an IR-cut filter to switch the camera from color to monochrome mode automatically by sensing the illumination level.

#### G. Power Requirements

1. Power shall be connected using the supplied power adapter or the Power over Ethernet (PoE).

2. The camera shall be capable of receiving power from 5V DC and IEEE802.3af Power over Ethernet (PoE).
3. The maximum power consumption shall be 5.52 W.

#### H. Environmental Requirements

1. The camera shall be able to tolerate between -20°C ~ 45°C (-4°F ~ 113°F) at startup and -30°C ~ 45°C (-22°F ~ 113°F) during operation.
2. The humidity shall be within the range of 10% to 90% with no condensation.
3. The camera shall comply with IP67 protection classification.
4. The camera shall comply with IK10 vandal resistance for metal casing.

#### I. System Requirements

1. The camera shall be accessible through Web browsers including Microsoft Internet Explorer (version 7.0 or later), Google Chrome, Mozilla Firefox and Safari.

#### J. Language Requirements

1. The camera shall support 31 languages on the Web interface, including Arabic, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Lithuanian, Norwegian, Persian, Polish, Portuguese, Romanian, Russian, Serbian, Simplified Chinese, Slovakian, Slovenian, Spanish, Swedish, Thai, Traditional Chinese and Turkish.

#### K. Applications

1. The camera shall support the following software for network storage:
  - Video management software: GV-System (GV-DVR/NVR), GV-VMS
  - Backup and Recording software: GV-Backup Center, GV-Recording Server
  - NAS system: GV-NAS System
2. The camera shall support smart device access using GV-Eye mobile app. for live viewing and remote playback.

3. The camera shall allow remote access from central management stations, such as GV-Control Center, GV-Center V2 and GV-Vital Sign Monitor.

L. Packing List shall include:

1. GV-Ultra Bullet Camera (with Waterproof or Non-Waterproof LAN connector)
2. Camera Stand
3. Black Rubber
4. Self Tapping Screw x 3
5. Plastic Screw Anchor x 3
6. Torx Wrench
7. Sun-Shield Cover Kit  
(1 Sun-Shield Cover, 2 Philips Head Screws, 2 Plastic Screw Spacers and 2 Hexagon Screws included)
8. Cable Connector (for waterproof LAN connector only)
9. Silica Gel Bag
10. 2-Pin Terminal Block
11. Data Cable
12. Power adapter
13. GV-IPCAM H.264 Quick Start Guide
14. GV-IPCAM H.264 Software DVD
15. GV-NVR Quick Start Guide
16. GV-NVR Software DVD

M. Certifications and Approvals

1. CE, FCC, RCM, RoHS Compliant